



Rotating Plate



Power Boost



3 Way Pay



Easy Dry

## Atlante 500

### Description

Atlante 500 is the new and standard-setting generation of free-standing vending machines for hot beverages – stunningly impressive from every angle. Its innovative U-Profile design with soft and elegant lines adds style to every room.

Along with its generous capacity (up to 550 cups), superb choice (up to 39 different products) and supreme convenience thanks to the revolutionary Saeco Rotating Plate system this vending wonder is perfect for medium locations.

Atlante 500 creates a perfect coffee corner for any context, stand-alone or combined with the snack&food machine Aliseo, and offers a complete solution for Vending. With the relative kit it can be transformed into Master in association with Aliseo Slave. Available in Espresso with double grinder, Espresso with one grinder and Instant versions.

### Accessories

- Independent water tank kit
- Mixer kit for tea replacement with soluble mixer
- Hot water solenoid valve kit
- Memory key to copy and quickly transfer machine settings
- USB key kit
- Eva-Dts kit
- Atlante Master transformation kit

### Main features

- Saeco Brewing Group with new pre-heating system Saeco Power Boost for excellent espresso (Espresso version)
- Generous container capacity
- Easy cleaning and maintenance thanks to the new Saeco Rotating Plate system
- Aesthetic and easily customizable U-Profile design with illuminated front
- User-friendly interface with LCD graphic display and easy-to-read and illuminated mechanical buttons
- Versatile dispensing area allowing cups with sizes up to 20 oz
- Possibility to install 3 payment systems on the door at the same time (Saeco 3 Way Pay)
- Accepts the most commonly used parallel and serial MDB, BDV and Executive (possible Master and Slave configurations) payment systems
- New powder dispensing system Saeco Easy Dry
- The machine is designed for easy use even by persons with disabilities

### User interface

- Direct access 15-button keypad for beverage selection
- 2 preselection keys: +/-sugar and 2 settable keys (decaffeinated/barley, no-cup and only-cup options)
- Graphic LCD

Technical data	Atlante 500 Espresso single grinder	Atlante 500 Espresso double grinder	Atlante 500 Instant
<b>Structural specifications</b>			
Dimensions (w x h x d)	646 x 1830 x 810 mm	646 x 1830 x 810 mm	646 x 1830 x 810 mm
Weight	160 kg	162 kg	150 kg
<b>Electrical specifications</b>			
Power supply	230 V/50 Hz	230 V/50 Hz	230 V/50 Hz
Power consumption	1700 W	1700 W	2300 W
<b>Water specifications</b>			
Boiler	1	1	1
Espresso boiler	brass (600 cc)	brass (600 cc)	
Instant boiler			stainless steel (3.2 l)
<b>Water connections</b>			
Water connection	3/4" (1 – 8 bar)	3/4" (1 – 8 bar)	3/4" (1 – 8 bar)
Water supply	standard: water supply optional: independent water tank kit	standard: water supply optional: independent water tank kit	standard: water supply optional: independent water tank kit
Independent water tank	2 tanks of 20 l	2 tanks of 20 l	2 tanks of 20 l
<b>Other specifications</b>			
Cups (h 70 mm)	550	550	550
Cups type ø	70 or 73 mm	70 or 73 mm	70 or 73 mm
Stirrers	550	550	550
Available stirrers	90 – 105 – 115 mm	90 – 105 – 115 mm	90 – 105 – 115 mm
Coffee bean container	1	2	
Instant product container	4	4	6
Sugar container	1	1	1
Number of selections	15	15	15
Number of preselections	2	2	2
Disc mixer	3	3	3
Spiral mixer	1	1	1
Brewing unit	7 gr or 9 gr	7 gr or 9 gr	
<b>Canisters capacity</b>			
Coffee beans	1 x 3.5 kg	2 x 2.6 kg	
Instant coffee	1.2 kg	1.2 kg	1.2 kg
Milk	1.3 kg	1.3 kg	1.3 kg
Chocolate	3.5 kg	3.5 kg	3.5 kg
Tea	4.0 kg	4.0 kg	4.0 kg
Sugar	4.5 kg	4.5 kg	3.0 kg

**Technical specifications**

- Pre-galvanized and painted steel-sheet body
- Containers and tanks in food-contact approved resin
- Saeco Rotating Plate system
- Riella lock
- Refill signal for water, coffee and cups
- Adjustable stirrer dispenser
- Electronically controlled boiler temperature
- Exhauster to absorb internal moisture and additional steam exhauster for the dispensing area
- Illuminated keypad, logo and promotional images
- Removable cup-releasing device for easy cleaning and checking
- 60 W electromagnetic vibration pump
- Anti-overflow air-break device
- Simplified error reset
- Built-in utility outlet
- Boiler safety valve
- General safety relay for 24 V components
- Thermal cut-outs on all devices supplied with line voltage
- Safety thermostat for boiler
- CE and VDE (Espresso version) approved



Aliseo  
+  
Atlante 500



Aliseo Slave  
+  
Atlante 500 Master